

APOLLO



APOLLO-S1



CANNOT SEE THIS PRODUCT IN
WWW.TOSPLIGHTING.COM
 Please provide the link

Available in:

Features & Benefits



- LED street light fitting with essential and clean design
- Available in 40w, 60w and 90w versions, with both S2, S3, S5 and S6 road optics



Specification

Ordering Code	Part Code	Description	Watts (W)	CRI	CCT* (K)	Input Voltage (VAC)	Fre-quency (Hz)	PF	LM/W	Lumens (lm)	Life (hrs)	Std Pack	Power Factor	Operating Temperature Range	Operating Humidity Range	IP Rating
RA10-40	500143014035001	Die cast Aluminium Street Light / LED	40	70	3500/4000/6500	220-240	50-60	0.95	130-150	6000	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66
RA10-60	500143016035001	Die cast Aluminium Street Light / LED	60	70	3500/4000/6500	220-240	50-60	0.95	130-150	9000	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66
RA10-90	500143019035001	Die cast Aluminium Street Light / LED	90	70	3500/4000/6500	220-240	50-60	0.95	130-150	13500	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66

APOLLO-S2



Features & Benefits

- Die cast aluminium body
- High lumen efficacy > 150 Lm/w
- Available in 120w, 140w and 160w options
- Pole mounting piece specially for vertical or horizontal mounting
- Provision of surge protection device 10 Kv - 10KA
- Designed for 220 - 240 v , 50 / 60 Hz AC with standard or dimmable drivers
- Available in 3000k, 4000k or 6000k Option

120W



140W



160W



Ordering Code	Part Code	Description	Watts (W)	CRI	CCT* (K)	Input Voltage (VAC)	Frequency (Hz)	PF	LM/W	Lumens (lm)	Life (hrs)	Std Pack	Power Factor	Operating Temperature Range	Operating Humidity Range	IP Rating
RA10-120	500143011235001	Die cast Aluminium Street Light / LED	120	70	3500/4000/6500	220-240	50-60	0.95	130-150	18000	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66
RA10-140	500143011535001	Die cast Aluminium Street Light / LED	140	70	3500/4000/6500	220-240	50-60	0.95	130-150	21000	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66
RA10-160	500143011635001	Die cast Aluminium Street Light / LED	160	70	3500/4000/6500	220-240	50-60	0.95	130-150	24000	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66