



CEILING

ACCESSORIES

CEILING ACCESSORIES

PLUG IN CEILING ROSE



FEATURES :

- Manufactured from high gloss polycarbonate body
- Screw type terminals
- Rated current 6Amp
- Insulating voltage 2KB
- Operating ambient temperature +50°C
- Maximum weight load 15Kg
- Cable capacity 0.75 – 1mm
- Flexible cord

FOUR TERMINAL CEILING ROSE



PENDANT SETS



FEATURES :

- Four terminal ceiling rose fitted with 6" long, flexible T-2 rated pendant holder E-27/B-22
- Four terminal ceiling rose fitted with 9" long, flexible T-2 rated pendant holder E-27/B-22
- Pendant Set - Ceiling rose fitted with 12" flexible cord & T2 rated B22/E27 lamp holder



PART NO	DESCRIPTION	RANGE	STANDARD	STD-PK
RPCR -1	PLUG IN TYPE CEILING ROSE	ALLIED ACCESSORIES	BS EN 60669-1	
RCR -1	CEILING ROSE FOUR TERMINAL	ALLIED ACCESSORIES	BS EN 60669-1	
RP6-B22	PENDANT SET 6" B22	ALLIED ACCESSORIES	BS EN 61184/BS 67/EN60598	
RP6-E27	PENDANT SET 6" E27	ALLIED ACCESSORIES	BS EN 61184/BS 67/EN60598	
RP9-B22	PENDANT SET 9" B22	ALLIED ACCESSORIES	BS EN 61184/BS 67/EN60598	
RP9-E27	PENDANT SET 9" E27	ALLIED ACCESSORIES	BS EN 61184/BS 67/EN60598	
RP12-B22	PENDANT SET 12" B22	ALLIED ACCESSORIES	BS EN 61184/BS 67/EN60598	
RP12-E27	PENDANT SET 12" E27	ALLIED ACCESSORIES	BS EN 61184/BS 67/EN60598	