



# DOOR ENTRY & PIR SENSORS



## DOOR BELLS & PIR OCCUPANCY SENSORS



### FEATURES:


- Impact resistant polycarbonate body
- Short circuit protection by PTC
- Built-in transformer 220-240V, 8V, -0.8Amp
- Decibel level 80DB
- Two notes chime sounds




### FEATURES:

- Ceiling mounted infrared sensor switch
- Rated capacity maximum load 16Amps, 250V AC for resistive load
- Delay time 5 / 30 / 1 / 3 / 5 / 20
- Infrared sensor
- Detection speed 0.1 – 3.0 m/sec
- Mounting height 2.4 – 3.6 meter (8 – 12 ft.)
- Optimal humidity maximum 100% RH
- Operating temperature -20°C to +50°C (-4°F to 122°F)
- Dimension 100 x 100 x 46mm
- Power supply 110/230 VAC as unit rated

Side View



Top View



PART NO	DESCRIPTION	RANGE	OPERATING VOLTAGE	STANDARD	STD-PK
RXT-3230P	DOOR BELL WITH PTC PROTECTION, W/O TRANSFORMER	DOOR ENTRY	250V AC	BS EN 60669-1	1
RXT-3230	DOOR BELL WITH TRANSFORMER	DOOR ENTRY	250V AC	BS EN 60669-1	1
RXT-3269	DOOR BELL WITH TRANSFORMER 220-12V	DOOR ENTRY	250V AC	BS EN 60669-1	1
RXTLC 360 HD	MOTION SENSOR CEILING MOUNTED 360°	ELECTRONICS	250V AC	BS EN 60669-1	1
RXTLC 363	MOTION SENSOR PYRAMID 360°	ELECTRONICS	250V AC	BS EN 60669-1	1
RXTOS-362D	MOTION SENSOR CEILING MOUNTED 360°	ELECTRONICS	250V AC	BS EN 60669-1	1
R780 S	MOTION SENSOR LINEAR	ELECTRONICS	250V AC	BS EN 60669-1	1