

LIGHTING

# HI-BAYS



**NOL SERIES HI BAYS**

Beam Angle

**RHB-150**



**RHB-100**



Ordering Code	Part Code	Color Temp. (K)	Beam Angle	Watts (W)	Power Factor	Luminous Flux(lm)	Voltage	Driver	Chip
RHB200	R50146-200W	5000-5500K	90°/110°	80	≥0.9	22000-24000 lm	AC90-305V	Mean Well	Nichia
RHB180	R50146-180W	5000-5500K	90°/110°	100	≥0.9	19800-21600 lm	AC90-305V	Mean Well	Philips
RHB150	R50146-150W	5000-5500K	90°/110°	120	≥0.9	16500-18000 lm	AC90-305V	Mean Well	Philips
RHB120	R50146-120W	5000-5500K	90°/110°	150	≥0.9	13200-14400 lm	AC90-305V	Mean Well	Philips
RHB100	R50146-100W	5000-5500K	90°/110°	180	≥0.9	11000-12000 lm	AC90-305V	Mean Well	Philips
RHB80	R50146-80W	5000-5500K	90°/110°	200	≥0.9	8800-9600 lm	AC90-305V	Mean Well	Philips

**NOL-RHB200T**



**NOL-RHB180T**



**NOL-RHB180T**



**NOL-RHB120T**



**NOL-RHB120T**



**NOL-RHB120T**



ORDERING CODE	PART NO	DESCRIPTION	STD. PACKING	MOQ	PRICE (US \$)	PRICE (Aed)
RHB200	R50146-200W	LED HIGHBAY-200W, 90-305V AC-50/60HZ	1			
RHB180	R50146-180W	LED HIGHBAY-180W, 90-305V AC-50/60HZ	1			
RHB150	R50146-150W	LED HIGHBAY-150W, 90-305V AC-50/60HZ	1			
RHB120	R50146-120W	LED HIGHBAY-120W, 90-305V AC-50/60HZ	1			
RHB100	R50146-100W	LED HIGHBAY-100W, 90-305V AC-50/60HZ	1			
RHB80	R50146-80W	LED HIGHBAY-80W, 90-305V AC-50/60HZ	1			

CE RoHS CB


**HIGH BAY -LED**

CE RoHS CB



WAREHOUSES, SUPERMARKETS, FACTORIES, LARGE STORES, FREEZER ROOMS AND SO ON.

- High quality spinning aluminium reflector
- Die-casting aluminium heat sink
- Self-designed electrical box
- Much higher CRI to HPS LPS MH
- Various Beam Angle
- IP65 available for outdoor application
- [Dimming available](#)



ORDERING CODE	PART NO	DESCRIPTION	STD. PACKING	MOQ	PRICE (US \$)	PRICE (Aed)
RHB90	R5114018-150	LED HIGHBAY - 90W, 100-300VAC-50/60HZ, 8500LM 5700K, 91 PCS LED	1	100		
RHB120	R5114018-150	LED HIGHBAY - 120W, 100-300VAC-50/60HZ, 11400LM 5700K, 119 PCS LED	1	100		
RHB150	R5114018-150	LED HIGHBAY - 150W, 100-300VAC-50/60HZ, 14000LM 5700K, 147 PCS LED	1	100		
RHB210	R5114102-210	LED HIGHBAY - 210W, 100-300VAC-50/60HZ, 19500LM 5700K, 210 PCS LED	1	100		


**Glowbrite High Bay 150W**



80° Reflector



120° Reflector



80° Polycarbonate Reeded Diffuser



Features

- High Output-17000Lm
- IP65 Rating
- 24Pcs Led, Cree LED
- Instant Light From Switch On (No Warm Up Or Cool Down Time)
- UL1598 Listed Suitable For Damp Locations



- **150W CREE High Output LED**
- **Choice Of Reflector**
- **6000K Colour Temperature/17000Lms**

ORDERING CODE	PART NO	DESCRIPTION	STD. PACKING	MOQ	PRICE (US \$)	PRICE (Aed)
	GLOWBRITE150CW-120D	GLOWBRITE HIGH BAY - 120° ALUMINIUM REFLECTOR				
	GLOWBRITE150CW-80D	GLOWBRITE HIGH BAY - 80° ALUMINIUM REFLECTOR				
	GLOWBRITE150CW-PRISM	GLOWBRITE HIGH BAY - 80° POLYCARBONATE REEDED DIFFUSER				

### 100W Constant Current Mode LED Driver



This 100W AC/DC LED driver featuring the circular shape design. It operates from 90~305V AC and offers the constant current output models with different rated voltage between 24V and 60V. The high efficiency up to 91.5% with fanless design, the entire series is able to operate for -40°C ~ +85°C case temperature under free air convection.

**Features**

- Constant current mode output
- IP67 / IP65 Rating for indoor or outdoor installations
- Built-in active PFC function
- Typical Lifetime > 50000 hours
- Function options: Output adjustable via potentiometer; 3 in 1 dimming (dim-to-off)

ORDERING CODE	PART NO	DESCRIPTION	STD. PACKING	MOQ	PRICE (US \$)	PRICE (Aed)
	HBG100	LED DRIVER 100W AC/DC	1	-	-	-

### 160W Constant Voltage + Current Mode LED Driver



160W AC/DC LED driver featuring the circular shape design. It operates from 90~305V AC and offers the dual modes constant voltage and current output models with different rated voltage between 24V and 60V. The high efficiency up to 93.5% with fanless design, the entire series is able to operate for -40°C ~ +85°C case temperature under free air convection. This

**Features**

- Constant voltage + current mode output
- IP67 / IP65 Rating for indoor or outdoor installations
- Built-in active PFC function
- Typical Lifetime > 50000 hours
- Function options: Output adjustable via potentiometer; 3 in 1 dimming (dim-to-off)

ORDERING CODE	PART NO	DESCRIPTION	STD. PACKING	MOQ	PRICE (US \$)	PRICE (Aed)
	HBG160	LED DRIVER 160W AC/DC	1	-	-	-

### HIGH BAY - METAL HALIDE



- High-purity aluminium reflector, providing excellent wide-angled light distribution
- Aluminium cast gear box
- Strengthened silicon seal
- stainless steel fixing hinge
- Protective glass cover made of 5mm toughened-glass



ORDERING CODE	PART NO	DESCRIPTION	STD. PACKING	MOQ	PRICE (US \$)	PRICE (Aed)
	PHB18E1/250MH-IP54	HIGH BAY 250watts	1	100		
	PHB18E1/400MH-IP54	HIGH BAY 400 watts	1	100		