





LED Panel Light - Blaze IP Series

Features & Benefits

- Recessed Application
- Supplied with External Driver
- Suitable for 85 – 265VAC
- Pf >0.9

Available in:

- 60 X 60cm in 36 / 40W,
- 30 x 30cm in 18W
- 30 X 120 in 36/42 W



Ordering Code	Part Code	Description	Watts (W)	CCT (K)	Voltage (VAC)	Frequency (Hz)	Beam Angle	CRI	L (mm)	W (mm)	Thickness (mm)	Lumens	Life (hrs)	Std Pack
RP66-40	R501150765-40	Blaze Square Panel 40W, 60x60	40	6500	100-240	50-60	120°	80	596	596	7.95	4150	50000	5
RP36	R501151265-36	Blaze Square Panel 36W, 60x60	36	6500	100-240	50-60	120°	80	596	596	10.5	3160	50000	4

*Available in 3000K



LED Panel Light - Flash Series






Features & Benefits

- Recessed Application
- Supplied with External Driver
- Suitable for 85 – 265VAC
- Pf >0.9

Available in:

- 60 X 60cm in 36 / 42W,
- 30 x 30cm in 18W
- 30 X 120 in 36/42 W
- P20



Ordering Code	Part Code	Description	Watts (W)	CCT (K)	Voltage (VAC)	Frequency (Hz)	Beam Angle	CRI	L (mm)	W (mm)	Thickness (mm)	Lumens	Life (hrs)	Std Pack
RP36F-36	R501151265-36	Flash Square Panel 36W, 60x60	36	6500	100-240	50-60	120°	80	596	596	10.5	3160	50000	4
RPF312-36	R501321265-36	Flash Rectangular Panel 36W, 30X120	36	6500	100-240	50-60	120°	80	300	1200	10.5	2990	50000	4

*Available in 3000K



LED Panel Light - Radiant Series




Features & Benefits


- Recessed Application
- Supplied with External Driver
- Suitable for 85 – 265VAC
- Pf >0.9

Available in:


- 60 X 60cm in 36 / 42W,
- 30 x 30cm in 18W
- 30 X 120 in 36/42 W



Radiant Square Panel 36W, 60x60



Radiant Rectangular Panel 42W, 30X120





Ordering Code	Part Code	Description	Watts (W)	CCT (K)	Voltage (VAC)	Frequency (Hz)	Beam Angle	CRI	L (mm)	W (mm)	Thickness (mm)	Lumens	Life (hrs)	Std Pack
RP33-18	R50130165-18	Radiant Square Panel 18W, 30X30	18	6500	100-240	50-60	120°	80	296	296	10.5	1440	50000	4
RP66-36	R50115165-36	Radiant Square Panel 36W, 60x60	36	6500	100-240	50-60	120°	80	596	596	10.5	3160	50000	4
RP66-42	R50115165-42	Radiant Square Panel 42W, 60x60	42	6500	100-240	50-60	120°	80	596	596	10.5	4150	50000	4
RP312-36	R50132165-36	Radiant Rectangular Panel 36W, 30X120	36	6500	100-240	50-60	120°	80	300	1200	10.5	2990	50000	4
RP312-42	R50132165-42	Radiant Rectangular Panel 42W, 30X120	42	6500	100-240	50-60	120°	80	300	1200	10.5	3925	50000	4

LED Panel Light - Flyer Series

Features & Benefits

- Recessed Application
- Supplied with External Driver
- Suitable for 85 – 265VAC
- Pf >0.9



Ordering Code	Part Code	Description	Watts (W)	CCT (K)	Voltage (VAC)	Frequency (Hz)	Beam Angle	CRI	L (mm)	W (mm)	Thickness (mm)	Lumens	Life (hrs)	Std Pack
RP66F-40	R50115865-36	Flyer Square Panel 40W, 60x60	40	6500	100-240	50-60	120°	80	596	596	7.95	4150	50000	5