

PICTOR



PICTOR



CANNOT SEE THIS PRODUCT IN
WWW.TOSPLIGHTING.COM
Please provide the link

Available in:

Features & Benefits






- Pressure die cast aluminium body
- Modular design in which LED modules are added to increase the lumen package
- Designed for voltage – 90 – 305 VAC
- Power factor > 0.95
- Lumen efficacy > 120 Lm / watt
- Suitable for side mounting application
- Available from 30 – 120w

APPLICATIONS:

Public areas - High way, city road, branch road, urban road etc.





Light Distribution Curve

Dimension Diagram

Specification

Ordering Code	Part Code	Description	Watts (W)	CRI	CCT* (K)	Input Voltage (VAC)	Frequency (Hz)	PF	LM/W	Lumens (lm)	Life (hrs)	Std Pack	Power Factor	Operating Temperature Range	Operating Humidity Range	IP Rating	LED Module
RP-30	500140013040001	Die cast Aluminium Street Light - LED	30	70	3000/4000/6500	100-240	50/60	0.95	130	3900	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66	36 module1
RP-60	500140016040001	Die cast Aluminium Street Light - LED	60	70	3000/4000/6500	100-240	50/60	0.95	130	7800	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66	36 module2
RP-90	500140019040001	Die cast Aluminium Street Light - LED	90	70	3000/4000/6500	100-240	50/60	0.95	130	11700	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66	36 module3
RP-120	500140011240001	Die cast Aluminium Street Light - LED	120	70	3000/4000/6500	100-240	50/60	0.95	130	15600	100,000	1	0.95	-40 ⁰ c - 50 ⁰ c	10%-90%RH	IP66	36 module3